

TEACHER INSTRUCTIONS

Fun with Liquid Nitrogen

Objective: To demonstrate the effects of temperature on the mechanical properties of materials by observing that many objects which are soft and malleable at room temperature become brittle when they are very cold.

Background Information: There are many real-world applications that put our understanding of the effects of temperature on materials to good use. A very well-known example is that of the Liberty ships, a type of cargo ship produced in large numbers by the United States during World War II. Many of the early ships used a variety of steel which became brittle and could crack at lower temperatures. Unfortunately, the cold water of the North Atlantic Ocean was below the temperature at which the steel became brittle, and as a result, a number of ships literally cracked in half! Another application for which temperature is important to consider is in turbine blades of jet engines. Jet engines burn fuel at such high temperatures that most normal metals would melt or become soft during operation. Therefore, jet engines that run at the highest temperatures often use ceramic turbine blades because they can better withstand the high temperatures without becoming warped or flexible.

Demo Description: In this demonstration, students will learn the difference between how some common items act at room temperature versus how they act after having been submerged in liquid nitrogen for a short time.

Keywords:

- temperature: a quantity which indicates how hot or cold a material is
- brittle: a material that breaks with little deformation when subjected to stress
- ductility: a solid material's ability to deform under tensile stress
- elasticity: the ability of a material to deform when loaded and then return to its original shape upon unloading
- plasticity: refers to the ability of a material to undergo permanent deformation without breaking

Materials List:

- liquid nitrogen
- styrofoam bowl (or some other well-insulating container)
- marshmallows
- rubber bands

- ping-pong balls
- sewing needle
- tongs
- insulating gloves
- safety glasses
- broom and dustpan
- hammer (OPTIONAL)

Safety Precautions: Liquid nitrogen is a hazardous substance. If misused, it may cause frostbite, eye damage, torn flesh, or asphyxiation. **ALWAYS FOLLOW THESE SAFETY RULES:**

- Keep liquid nitrogen away from students.
- Wear safety goggles at all times.
- Use tweezers to handle superconductors, magnets, or other small, cold objects. Plastic tweezers are desired but should be tested for embrittlement (see last caution) before use in the classroom.
- Wear insulating gloves when handling liquid nitrogen containers or large, cold objects.
- Use liquid nitrogen only in well-ventilated places.
- Do not allow liquid nitrogen to touch any part of your body.
- Items in contact with liquid nitrogen become **EXTREMELY COLD**. Do not touch any item that has been immersed in liquid nitrogen until it has warmed to room temperature.
- Do not store liquid nitrogen in any container with a tight-fitting lid. A tightly sealed container will build up pressure as the liquid boils and may **EXPLODE** after a short time.
- Many substances become brittle and may shatter when cold, sending pieces of the material flying. Avoid common glass and large, solid plastics.

Instructions:

1. While wearing gloves, pour some liquid nitrogen into the styrofoam bowl.
2. Submerge a rubber band in the liquid nitrogen for about one minute.
3. Remove the rubber band and hold it at one end with the tongs. Ask that a student put on a glove and attempt to stretch it. Observe that it snaps in a brittle manner.
4. Repeat step 2 with a marshmallow.
5. Remove the marshmallow. Drop it on the floor and observe it shatter.
6. Very carefully puncture a ping pong ball with the sewing needle and repeat step 2.
7. Remove the ping pong ball and place it on the floor or table. As the air inside warms back to room temperature, it expands and releases from the small hole, causing the ball to spin.

Demo Delivery Hints: The above items were chosen primarily due to their low cost and their ability to demonstrate some key mechanical property changes in materials. Feel free to augment the recommended items with others of your choice. Additional objects of interest might include fruit (such as grapes or bananas), flowers, or balloons inflated with air. The latter can be used to show the remarkable volume change experienced by a gas over a temperature range. You could also use the ideal gas law to quantify that volume change.

Troubleshooting: If the objects dropped to the floor do not shatter readily, a hammer can be used to shatter the objects. Place the objects on a hard surface that will not be damaged by the hammer and take extra precautions with finger and eye protection.

Cleanup/Replacement parts: Dispose of the liquid nitrogen by either letting it boil away completely, or for a bit more excitement, pour it carefully onto the floor where the liquid will form small spheres that will scatter and dissipate quickly. Make sure the shattered objects have warmed to room temperature, and then use the broom and dustpan to sweep up the pieces.

TEACHER DISCUSSION QUESTIONS

Fun with Liquid Nitrogen

Discussion Questions to Ask Before the Demo

1. Ask students to give examples of how materials deform when a force is applied to them.

Discussion: Materials generally deform in one or both of two ways: in an elastic manner or a plastic manner. Perfectly elastic materials, like rubber bands at room temperature, can be deformed (stretched) by a force, but will return to their original shape when the force is removed. Perfectly plastic materials, like silly putty at room temperature, change shape when a force is applied and remain in that shape even after the force is removed. Most materials deform in a way that is a combination of the two. For example, squish a fresh marshmallow. It will flatten out because of the force applied by your fingers. When you stop applying the force, you may notice that the marshmallow tries to puff back to its original shape, but it doesn't quite get there. The marshmallow's attempt to puff back to its original shape is the elastic component of its deformation, while the leftover flattening is the plastic component of its deformation.

2. Ask students to give examples of how materials break.

Discussion: Materials generally break in one or both of two ways as well: in a brittle manner or a ductile manner. In a 100% brittle material, such as a coffee mug, the constituents of the material (atoms in the case of a coffee mug) cannot rearrange themselves easily when a force is applied and therefore the bonds between them fracture. In a 100% ductile material, like silly putty, the constituents of the material (polymer chains in the case of silly putty) can easily slide over one another and eventually the material stretches so thin that no more material is left to slide over itself, and it becomes two pieces. As with deformation, most materials break in a way that is a combination of the two. If you pull a marshmallow fast enough at room temperature it will stretch some as the sugar molecules slide over one another, but it will then “snap” in two. The stretching is the tendency of the marshmallow to break in a ductile manner, while the “snap” is the tendency of the marshmallow to break in a brittle manner.

3. Ask students how they think changing temperature will affect how materials deform and break.

Discussion: When discussing how materials break, it was noted that brittle materials are brittle because the constituents of the material cannot rearrange. What factor determines the ease of that rearrangement? Temperature is the answer in most cases. Temperature is

a measure of thermal energy, which in turn is essentially how much and how fast atoms in the material vibrate back and forth. When a force is applied to a material, the material's thermal vibrations can let the material's constituents hop or slide over each other, allowing for plastic deformation and a tendency towards breaking in a ductile manner. For the same reason, a material with less thermal energy cannot as easily let its constituents hop or slide, so the material has a tendency towards breaking in a brittle manner. So, you would probably expect materials to become more brittle as the temperature decreases.

4. Ask students why it is important for engineers to think about temperature when selecting materials for specific purposes.

Discussion: See the Background Information section in the Teacher Instructions for discussion of this question.

Discussion Questions to Ask During the Demo

1. Ask students to guess how each object will behave before subjecting the object to a test.

Discussion: There is no right or wrong answer to this question. Encourage as much discussion as possible as this is the best way to get students interested in the demo.

2. Ask students to note how each object behaves or breaks after testing.

Discussion: See the explanation of brittle/ductile and elastic/plastic and the influence of temperature discussed in Questions 1-3 above. Encourage students to make the connection about the change in material properties (e.g., moving from ductile to brittle when exposed to liquid nitrogen, elastic to plastic, etc.) that they observe when a material is subjected to liquid nitrogen.

Discussion Questions to Ask After the Demo

1. Ask students to compare the behaviors of the rubber band at room temperature versus at 77 K.

Discussion: Both objects break in a very brittle manner because neither has enough thermal energy to plastically or elastically deform (only small atomic scale deformations occur). At room temperature, rubber bands can stretch because they are comprised of coiled polymer chains (like springs) that uncoil and recoil when a force is applied and removed. At 77 K, the polymer coils do not have enough thermal energy to uncoil themselves. Therefore, only the bonds between individual atoms in the polymer chains can stretch. The bonds between each polymer chain are much weaker than the bonds

between atoms, resulting in the rubber band breaking as soon as the forces on the chains exceed the chain-chain bond strength. Interestingly, the rubber band still deforms elastically, but only the smallest amount on the atomic scale rather than on the larger chain scale. Ceramic materials behave similarly. Most people do not consider ceramics to be elastic, but in general, ceramics can ONLY deform elastically. The deformation from stretching atomic bonds in ceramics requires large forces and results in such little strain (overall lengthening or shortening of an object) that you cannot detect it without sophisticated measurement techniques.

2. Ask students to compare the behavior of the marshmallow and the other objects at room temperature versus at 77 K.

Discussion: In a similar way to the rubber bands, the marshmallow breaks in a brittle manner at 77 K. It retains neither its elasticity nor plasticity.

3. Ask students to think about the fact that real engineering materials, like steel at room temperature, might be analogous to the marshmallow at 77 K. Ask them to hypothesize how a steel would behave if its temperature were raised to 2000°F (roughly 70% of a typical steel's melting point).

Discussion: As you might expect, the steel will become softer and easier to deform at higher temperatures. Steel that might otherwise break in a mostly brittle manner may break in a highly ductile manner at 70% of its melting temperature. Eventually, at a high enough temperature, the steel will sag under its own weight, similar to silly putty. As mentioned in the Background Information section, steel is one of the most commonly used materials for engineering applications. If it is too cold, it will be too brittle, and if it is too hot, it may be too ductile. The key is to strike the right balance.

STUDENT QUESTION HANDOUT

Fun with Liquid Nitrogen

1. How does the rubber band behave at room temperature?
2. How does it behave after being subjected to liquid nitrogen?
3. What caused this behavior?
4. How does the marshmallow behave at room temperature?
5. How does it behave after being subjected to liquid nitrogen?
6. What happened to the ping pong ball after it was removed from the liquid nitrogen?
7. Why do you think this happened?

The American Ceramic Society Materials Science Kits Warranty Disclaimer, Limitation of Liability and Safety Disclaimer

NO WARRANTY – DISCLAIMER OF WARRANTY

THE AMERICAN CERAMIC SOCIETY (ACerS), OFFERS THE MATERIALS SCIENCE KITS “AS-IS”, WITH NO WARRANTIES WHATSOEVER, EXPRESS OR IMPLIED, INCLUDING, WITHOUT LIMITATION, WARRANTIES OF MERCHANTABILITY, SAFETY, FITNESS FOR ANY PARTICULAR PURPOSE OR NON-INFRINGEMENT OF PATENTS, COPYRIGHTS OR OTHER PROPRIETARY RIGHTS OF OTHERS. SOME STATES AND JURISDICTIONS DO NOT ALLOW LIMITATIONS ON IMPLIED WARRANTIES, SO THE ABOVE LIMITATIONS MAY NOT APPLY TO CUSTOMER. WHEN THE IMPLIED WARRANTIES ARE NOT ALLOWED TO BE EXCLUDED IN THEIR ENTIRETY, THEY WILL BE LIMITED TO THE SHORTEST DURATION PERMITTED UNDER APPLICABLE LAW. CUSTOMER MAY ALSO HAVE OTHER RIGHTS WHICH VARY FROM STATE TO STATE.

WITHOUT LIMITING THE GENERALITY OF THE FOREGOING, ACerS DOES NOT WARRANT THAT EACH MATERIALS SCIENCE KIT IS COMPLETELY ERROR FREE, WILL OPERATE WITHOUT INTERRUPTION, OR IS COMPATIBLE WITH ALL EQUIPMENT AND SOFTWARE CONFIGURATIONS. CUSTOMER EXPRESSLY ASSUMES ALL RISK FOR USE OF THE MATERIALS SCIENCE KITS.

LIMITATION OF LIABILITY

TO THE MAXIMUM EXTENT PERMITTED BY LAW, ACerS WILL NOT HAVE ANY LIABILITY OR RESPONSIBILITY TO CUSTOMER FOR DAMAGES OF ANY KIND, INCLUDING SPECIAL, INDIRECT OR CONSEQUENTIAL DAMAGES (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF DATA), ARISING OUT OF OR RESULTING FROM THE MATERIALS SCIENCE KITS, ANY COMPONENT, DOCUMENTATION, SERVICES OR MATERIALS MADE AVAILABLE TO CUSTOMER IN CONNECTION WITH THE MATERIALS SCIENCE KITS OR THE USE OR MODIFICATION OF ANY OF THEM, EVEN IF ACerS HAS BEEN ADVISED OF THE POSSIBILITY OF THE DAMAGES. IN ANY CASE, ACerS AND ITS LICENSORS' ENTIRE LIABILITY UNDER ANY PROVISION OF THIS AGREEMENT WILL BE LIMITED TO THE AMOUNT ACTUALLY PAID BY CUSTOMER TO ACerS FOR THE PRODUCT OR TEN DOLLARS (\$10.00), WHICHEVER IS GREATER. Some states do not allow the limitation or exclusion of liability for incidental or consequential damages, or have legislation which restricts the limitation or exclusion of liability, so the above limitation may not apply to Customer.

CALIFORNIA RESIDENTS

California Residents: I understand that I am waiving rights with respect to claims that are at this time unknown or unsuspected, and in accordance with such waiver, I acknowledge that I have read and understand, and I hereby expressly waive, the benefits of section 1542 of the civil code of California, and any similar law of any state, country or territory, which provides as follows: “A general release does not extend to claims which the creditor does not know or suspect to exist in his or her favor at the time of executing the release, which if known by him or her must have materially affected his or her settlement with the debtor.”

MATERIALS SCIENCE SAFETY DISCLAIMER

The materials science kits contain lessons that are believed to be reliable regarding the safe use and handling of these materials in laboratories and student classrooms. ACerS, however, does not represent or warrant in this, or in any other publication, to specify minimum safety or legal standards or to address all of the compliance requirements, risks, or safety problems associated with the handling of hazardous materials, their use, or the methods prescribed for using them in laboratories or classrooms. This information is intended to serve only as a beginning point for information and should not be construed as containing all the necessary compliance, safety, or warning information, nor should it be construed as representing the policy of ACerS. The kits should be used by minors (under 18) only with adult supervision.

Without limiting the generality of the foregoing disclaimers, no warranty, guarantee, or other form of representation is made by ACerS as to the accuracy or sufficiency of the information and guidelines included with the materials science kits, and ACerS assumes no liability or responsibility concerning the use of such instructions and guidelines for any purpose. It is the responsibility of the users of these materials to consult and comply with pertinent local, state, and federal laws, regulations, and standards with respect to the handling of materials. Users of the materials science kits should consult with the school's legal counsel or other professional advisers about the applicable laws, safety issues, and compliance issues for the storage of materials and the methods for using the materials in school classrooms and laboratories.

THIS DISCLAIMER APPLIES TO ANY LIABILITY THAT IS, OR MAY BE INCURRED BY, OR ON BEHALF OF THE INSTITUTIONS THAT USE THE MATERIALS SCIENCE KITS; INCLUDING, WITHOUT LIMITATION, THE FACULTIES, STUDENTS, OR PROSPECTIVE STUDENTS OF THOSE INSTITUTIONS; AND ANY MEMBER OF THE PUBLIC AT LARGE; AND INCLUDES, BUT IS NOT LIMITED TO, A FULL DISCLAIMER OF ANY LIABILITY THAT MAY BE INCURRED WITH RESPECT TO POSSIBLE INADEQUATE SAFETY PROCEDURES TAKEN BY ANY USER.

TEACHER INSTRUCTIONS

Superconductivity

Objective: To demonstrate the basic properties of superconducting materials and to provide a basic understanding of superconductivity and some of its applications.

Background Information: Superconductivity was discovered in 1911 by Kamerlingh Onnes, after he became the first person to successfully liquefy helium (helium liquefies at a temperature of -269°C , a temperature difficult to attain with the scientific equipment available at the time). The ability to reach such low temperatures led him to explore the electrical properties of metals at temperatures close to absolute zero. It was well known that the resistivity of metals decreased with decreasing temperature in the higher temperature ranges (now known to be because the conducting electrons are less impeded by thermal vibrations of atoms). However, it was not clear what the resistance of a metal would do at extremely low temperatures. Three theories existed at the time: 1) the resistance would drop to zero at 0 K, 2) the resistance would flatten out to a constant value at 0 K, and 3) the resistance would increase to infinity at 0 K because the electrons themselves would “freeze”. Upon testing mercury, Onnes discovered that its resistance suddenly dropped to an immeasurably low value at about 4.2 K. In fact, the resistance disappeared completely. This phenomenon, dubbed superconductivity because a zero-resistance material can conduct a current with no loss of energy to heat, results in a number of interesting and potentially useful behaviors.

The zero-resistance state of a superconductor is the result of a complex set of interactions between the electrons and the atoms of the material. However, on a conceptual level, the behavior can be explained as a resonance between pairs of electrons and vibrations in the material's lattice of atoms (called phonons when the vibrations have a regular frequency). There is an overall energy savings by allowing for electrons to pair up, and this electron coupling results in zero resistance. However, coupling can only happen when the electron-scattering effect of random thermal vibrations is reduced at very low temperatures.

Unlike conventional conductors whose current can be related to resistance through Ohm's law, current in superconductors is strongly tied to the magnetic field in the material. Materials in a Type-I superconducting state allow for no magnetic flux lines to pass through, channeling them to the outside like a boulder diverts current in a river (The material used in this demonstration, YBCO, is a Type-II superconductor which can remain superconducting while allowing some magnetic flux lines to pass through it. The theory for describing Type-II superconductivity is